

CLEAR CHOICE AT60N

FILM APPLICATION TAPES

AT60n consists of a matte finish, polypropylene film with excellent clarity, coated with an acrylic adhesive designed for clean pick up and transfer of all brands of cast or calendered vinyl. A unique polymerization process of acrylic adhesive assures a water-resistant and static free application tape. The stable adhesive will not build in tack level when applied to vinyl graphics for extended periods of storage.

TECH DATA SHEET

PHYSICAL SPECIFICATIONS

Adhesive	Acrylic
Color	Transparent
Caliper <i>facestock</i>	93 microns (3.7 mils)
Adhesion to Steel*	1 - 4 N/100mm (1 - 3oz.)
Tensile	25MPa (3600psi)
Elongation	700
Shelf Life**	1 Year
Base	{tag_base}

FEATURES

- The excellent water resistance of the acrylic adhesive allows for wet application without leaving any adhesive residue on the vinyl.
- A static free adhesive improves the lamination process.
- Exceptional clarity to aid precise registration of multi-color overlays.
- Easy unwind eliminates exhausting application tape struggles.
- Rigid polypropylene facestock minimizes misalignment problems.
- Excellent lay flat to resist curling.
- Unique adhesive system will not build to vinyl during storage of graphics.
- Forgiving adhesive system allows the user to pull apart the tape easily, if the film accidentally folds onto itself!

Leveringen geschieden uitsluitend volgens onze Algemene Voorwaarden. Zie <http://www.herante.com/voorwaarden>